





## FN Bearing Machinery Equipment Co.,Ltd

Reference speed	5300 r/min
Limiting speed	5300 r/min
Calculation factor - $k_r$	0.1
Calculation factor - $k_a$	1.6
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - $Y_0$	0.52
Calculation factor - $Y_1$	0.55
Calculation factor - $Y_2$	0.93
Calculation factor - X	0.35
Calculation factor - $Y_0$	0.26
Calculation factor - $Y_1$	
Calculation factor - $Y_2$	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.723
EAN	7316577610652
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	CB



## FN Bearing Machinery Equipment Co.,Ltd

Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	70MM Bore; 150MM Outside Diameter; 35MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; CB; Steel Cage; 40 Degree; 1 (Single); Univers
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7314 BECBJ
Outside Diameter	5.906 Inch   150 Millimeter
Width	1.378 Inch   35 Millimeter
Bore	2.756 Inch   70 Millimeter
bore diameter:	70 mm
radial static load capacity:	90 kN
outside diameter:	150 mm
outer ring width:	35 mm
overall width:	35 mm
maximum rpm:	5300 RPM
contact angle:	40 °
finish/coating:	Uncoated
row type & fill slot:	Single-Row Non-Fill Slot
precision rating:	Not Rated
internal clearance:	C0



## FN Bearing Machinery Equipment Co.,Ltd

fillet radius:	2 mm
closure type:	Open
series:	73
radial dynamic load capacity:	119 kN
$d_1$	101.1 mm
$d_2$	84.4 mm
$D_1$	121.5 mm
$r_{1,2}$ min.	2.1 mm
$r_{3,4}$ min.	1.1 mm
$d_a$ min.	82 mm
$D_a$ max.	138 mm
$D_b$ max.	143 mm
$r_a$ max.	2 mm
$r_b$ max.	1 mm
Basic dynamic load rating C	127 kN
Basic static load rating $C_0$	98 kN
Fatigue load limit $P_u$	3.9 kN
Calculation factor A	0.145
Calculation factor $k_r$	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor $Y_0$	0.26
Calculation factor $Y_2$	0.57
Calculation factor X	0.57
Calculation factor $Y_0$	0.52
Calculation factor $Y_1$	0.55
Calculation factor $Y_2$	0.93
Mass bearing	2.65 kg